

PRODUCT TECHNICAL SPECIFICATIONS - WATER DISPENSERS

PARTICULARS	Unit	I Sense	SS 1515 Fountain	Instafresh Sensor	Lagunafresh (FSCC)	Lagunafresh (FS)	Lagunafresh (Sensor)	Instafresh White Wine Red / Jet Black FS	Instafresh White Wine Red / Jet Black FS	Instafresh (TT)	Aquagenie+ (FSCC)	Aquagenie+ (FS)	Aquagenie+ (FSCC)	Aquagenie+ (TT)
NUMBER OF FAUCET	Nos	2	1	3	1	1	1	3	3	3	3	3	3	3
REFRIGERANT	-	CFC Free eco-friendly R-134a Refrigerant	R-134a (Non CFC) Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant
POWER SUPPLY	-	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC	230 V ± 10%, 50 Hz Single Phase AC
PRODUCT DIM.	LxWxH	270mmx420mmx 1.3m	350mmx1.03m (DiaxH)	31cmx31.5cmx93.4cm	310mmx370mmx1.01m	310mmx350mmx1.01m	310mmx350mmx1.01m	31cmx31.5cmx 93.4cm	31cmx31.5cmx 93.4cm	31.3cmx35cmx 50.6cm	38cmx32cmx 1m	38cmx32cmx 1m	38cmx32cmx 1m	38cmx32cmx 51cm
NET WEIGHT	kg	14.5	-	12.1	17.8	14	14	14.3	12.1	9.95	18.4	16	17	12.6
GROSS WEIGHT	kg	17.3	-	14.18	19.85	16	16	16.7	14.18	11.45	20.7	18.2	19.5	14.1
POWER CONSUMPTION	W	90 W, 580 W	390 W	90 W, 500 W	100 W/ 500 W	100 W/ 500 W	100 W/ 500 W	100 W/ 500 W	90 W/ 500 W	90 W/ 500 W	120 W/ 500 W	100 W/ 500 W	100 W/ 500 W	100 W/ 500 W
COOLING	W	90 W	390 W	90 W	100 W	100 W	100 W	100 W	90 W	90 W	120 W	100 W	100 W	100 W
HEATING	W	580 W	-	500 W	500 W	500 W	500 W	500 W	500 W	500 W	500 W	500 W	500 W	500 W
RATE OF COOLING	L/h	2.5	15	3	3	3	3	3	3	3	2.5	2.5	2.5	2.5
RATE OF HEATING	L/h	4	-	5	5	5	5	5	5	5	5	5	5	5
STORAGE CAPACITY	L	3 L , 1 L	15 L	3 L , 1 L	3 L , 0.9 L	3 L , 0.9 L	3 L , 0.9 L	3 L , 1 L	3 L , 1 L	3 L , 1 L	3.2 L , 1 L	3.2 L , 1 L	3.2 L , 1 L	3.2 L , 1 L
COLD	L	3 L	15 L	3 L	3 L	3 L	3 L	3 L	3 L	3 L	3.2 L	3.2 L	3.2 L	3.2 L
HOT	L	1 L	-	1 L	0.9 L	0.9 L	0.9 L	1 L	1 L	1 L	1 L	1 L	1 L	1 L

KEY FEATURES

KEY FEATURES 01	1.3 m Tall height for easy dispensing to prevent backache problems	Cooling & storage capacity of 15 L	Sensor technology for contactless dispensing	Fridge cabinet capacity 20 L	--	Sensor-based water dispensing for Hot, Normal and Cold water	18 L Cooling cabinet with temperature upto 14°C for storing beverages	--	Compact Design suitable to place on table	18 L Cooling cabinet with temperature upto 14°C for storing beverages	--	18LStorage cabinet	Compact Design suitable to place on table
KEY FEATURES 02	Water Dispensing In 200 ml/300 ml/400 ml /500 ml Capacity For measuring everyday glass of health	Swan neck for comfortable use	Compact and sleek design suitable for office or household	Cooling capacity 3L / h < 15°C at 35°C ambient	Cooling capacity 3L / h < 15°C at 35°C ambient	Single faucet for Hot, Cold, and Normal water dispensing	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting
KEY FEATURES 03	Digital control water dispensing Hot water: up to 85°C, Cold water:up to 15°C	Inbuilt 30 mins power backup for continuous water supply	Individual faucets for hot, normal and cold water for ease of operation	Heating capacity 5L/h, 85±5°C	Heating capacity 5L/h, 85±5°C	CFC Free eco-friendly R-134a Refrigerant	Designed for efficient cooling even in hot indian conditions	Designed for efficient cooling even in hot indian conditions	Designed for efficient cooling even in hot indian conditions	Safety mesh for rodent control	Safety mesh for rodent control	Safety mesh for rodent control	Safety mesh for rodent control
KEY FEATURES 04	Bottom loading water bottle compartment to avoid heavy weight lifting	Compact design suitable for modern décor	Anti-rust faucets	CFC Free eco-friendly R-134a Refrigerant	Single faucet for Hot, Cold, and Normal water dispensing	Heating capacity 5L/h, 85±5°C	Safety lock onhot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet
KEY FEATURES 05	CFC Free eco-friendly R-134a Refrigerant	--	CFC Free eco-friendly R-134a Refrigerant	Single faucet for Hot, Cold, and Normal water dispensing	CFC Free eco-friendly R-134a Refrigerant	Cooling capacity 3L / h < 15°C at 35°C ambient	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant
KEY FEATURES 06	--	--	--	Compact & Dual tone finish	Compact & Dual tone finish	Compact & Dual tone finish	--	--	--	--	--	--	--

USHA care
Toll free
1800-1033-111

www.usha.com
usha_care@usha.com
http://www.facebook.com/ushainternational

USHA®

WATER SOLUTIONS

EXPERIENCE
WATER COMING TO LIFE
WITH
SUPERIOR TECHNOLOGY
PRESENTING
WATER DISPENSER RANGE



Sensor Based
Dispensing



Child Lock
On Hot Water
Faucets



Eco-Friendly
Refrigerant



Low Power
Consumption



Technology You Can Trust.

Made tough to outperform

Usha water dispensers are perfect choice for your office space, promising best in class cooling while consuming less power.



I SENSE



LAGUNA FRESH FSCC



LAGUNA FRESH FS

*Comes in Sensor based Technology also.



SS1515



AQUAGENIE+ FS




AQUAGENIE+ FSCC

OUR TECHNOLOGY



*SENSOR BASED
CONTACTLESS
DISPENSING



FOOD-GRADE
PLASTIC



INDIVIDUAL FAUCETS
FOR HOT, NORMAL
AND COLD WATER




HIGH-QUALITY
STAINLESS STEEL
TANK




INLET
HOSEPIPE



RELIABLE
RECIPROCATING
COMPRESSOR



COMPACT AND
SLEEK DESIGN
TO FIT INTO ANY
SETTING



LOW POWER
CONSUMPTION



REFRIGERANT
R134A



INSTAFRESH FS (WINE RED)



INSTAFRESH FSCC (WINE RED)



INSTAFRESH FS (JET BLACK)



INSTAFRESH FSCC (JET BLACK)



INSTAFRESH FS



INSTAFRESH FSCC



INSTAFRESH TT

*Actual faucet design may differ.